# **TC Series**

# **Tire Changers**

### SITE REQUIREMENTS



	TC39 Family	TC37 Family
Electrical Circuit Requirements	208-230V, 8A, 50/60Hz, 1 ph NEMA 20 amp plug, L6-20P	
Air Supply Requirements	115-145 psi (8-10 bar)	
Base Machine Weight	914 lbs (415 kg)	911 lbs (413 kg)
Wheel Lift Weight	91 lbs (41 kg)	
Side Shovel Weight	91 lbs (41 kg)	
Width (W)	54 in. (1,372 mm)*	
Height (H)	77 in. (1,956 mm)	72 in. (1,829 mm)
Depth (D)	57 in. (1,448 mm)	

\* Add 14 in. (356 mm) for maximum side shovel opening (if equipped)

TC37 Family

# KEY SPECIFICATIONS



	1000 Failing	
Mount / Demount Tool	Polymer Self-inserting leverless	Polymer Standard lever mount head
Clamping Type	Center w/ Quick Clamp and Cam Plate	
Bead Loosening Type	Upper & Lower Rollers (Shovel Optional)	
Match Mounting Capable	Yes	
Adjustable Clamping Height	Yes, 3 position	
Rim Diameter Range	10-26 in.	
Maximum Tire Diameter	46 in.	
Maximum Wheel Width	19 in.	
Drive Speed	Fully Variable, 0-14 RPM Clockwise Single Speed, 7 RPM Counterclockwise	
Drive Torque	867 ft-lb (1175 N-m)	
Wheel Lift Capacity (if equipped)	176 lbs (80 kg)	

TC39 Family



Because of continuing technological advancements, specifications, models and options are subject to change without notice.



#### For tire changer information visit: www.hunter.com/tire-changers

For local contact visit: www.hunter.com/contact-hunter

For general inquiries visit: www.hunter.com or call 800-448-6848

Form 6378-T, 2-20 Supersedes Form 6378-T, 05-18b Copyright © 2011-2020, Hunter Engineering Company

